

# American Data Link

## 22AWG 3-Conductor Stranded White Cable

### Technical Data Sheet



**Manufacturer Part Number:** 223X-WH-SPEC-NRC  
**Inspired LED SKU# 8599-B** (Bulk, sold by ft.)

**Description:** 3-Conductor 22 AWG stranded bare copper, insulated and jacketed with an overall white sunlight resistant jacket, **with no rip cord**

**NEC Rating:** CMR and FPLR -NEC Articles 800 and 760

**Approvals:** c(ETL)us Listed to UL Standards 444 and 1424  
Certified to CSA Std. C22.2 No. 214+B4  
Complies with European Directive 2002/95/EC RoHS  
P-MSHA approved – CFR Title 30, Part 7, Subpart K, Section 7.408

**Flame Rating:** UL 1666 Riser Flame Test

**Application:** Fire alarm power-limited circuit cable and/or communications cable used for riser applications

**Construction:**

<b>Number of Conductors-</b>	3
<b>Size and Stranding-</b>	22AWG (7 Strand) Bare Copper
<b>Insulation Material (Nom.)-</b>	0.010" PVC
<b>Color Code-</b>	Black, White and Yellow
<b>Jacket Material-</b>	0.015" White Sunlight Resistant PVC
<b>Overall Cable Diameter-</b>	0.136"

**Print Legend:** AMERICAN DATA LINK #223X-WH-SPEC-NRC 3COND 22AWG FPLR/CMR  
c(ETL)us 75C SUN RES RoHS P-07-KA090003-MSHA 300V **MADE IN THE USA**

**Environmental & Electrical Properties:**

<b>Temperature Rating-</b>	-20°C to 75°C
<b>Operating Voltage (Max)-</b>	300 V RMS
<b>Nom. Capacitance btw Cond. @ 1KHz-</b>	25 pf/ft
<b>Nom. DC Resistance per Cond @ 20 C-</b>	17.5 Ohms per 1000 ft

*The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond ADL control, all recommendations or suggestions are presented without guarantee or responsibility on our part. ADL and their distributors disclaim all liability in connection with the use of information contained herein or otherwise.*